# MetsäBoard Pro FBB Bright

# **PRODUCT SHEET**



## **Product description**

Fully coated bleached paperboard with white reverse side

## End use

Chocolate and confectionery, Foods, Healthcare, Graphic applications, Beautycare, Consumer electronics, Covers, Cards, Beverages, Point-of-sales materials

#### **Features**


Printing method Offset, Digital, Gravure, Flexo Food contact EU Regulation (EC)

No 1935/2004.

USFDA21CFR§176.170\*, USFDA21CFR§176.180\*

Metsä Board mill Äänekoski, Husum

### Structure



- 1) Multiple blade coating
- 2) Bleached chemical pulp
- Bleached chemi-thermomechanical pulp (BCTMP)
- 4) Bleached chemical pulp

PROPERTY, UNIT	METHOD	STANDARD	TOLERANCE									VALUES							
Grammage		ISO 536	± 2%	180	195	220	230	245	255	265	280	290	320	350					
Thickness µm		ISO 534	± 3%	260	305	355	385	415	435	455	485	505	555	610					
Bending stiffness CD (Taber 15°)	Taber 15°	ISO 2493-2	- 15%	2.4	3.8	5.4	6.6	8.1	9.0	10.0	11.6	13.0	16.0	19.0					
Bending stiffness MD (Taber 15°)	Taber 15°	ISO 2493-2	- 15%	5.2	7.8	11.0	13.5	16.5	18.4	20.2	23.3	26.3	32.5	38.0					
Moisture content %		ISO 287	± 1.0	6.8	7.0	7.0	7.2	7.5	7.7	7.7	7.8	8.1	8.3	8.5					
Smoothness top µm	PPS10	ISO 8791-4	max 1.3	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0					
Brightness top %	Illumination C/2°	ISO 2470-1	± 1	91	91	91	91	91	91	91	91	91	91	91					
Colour CIELAB L* top	Illumination C/2°	ISO 5631-1	± 1.0	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8	95.8					
Colour CIELAB a* top	Illumination C/2°	ISO 5631-1	± 0.5	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6					
Colour CIELAB b* top	Illumination C/2°	ISO 5631-1	± 1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0	-1.0					
Gloss %	Hunter 75°	ISO 8254-1	± 5	48	48	48	48	48	48	48	48	48	48	48					
Off-flavour (Robinson test)	12 mo in orig. pack	EN 1230-2		< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1	< 1					

Tolerances, when specified, are based on 95% confidence limits on mill measurements of samples tested in standard conditions (23°C/50% RH). Metsä Board Paperboard mills have FSC® / C001580 and PEFC / 02-31-92 CoC certificates.

<sup>\*</sup>Please contact Metsä Board for details of grammage and / or country-specific, restrictions and limitations. Issued 02.07.2020. Supersedes sheet dated 24.04.2019.